






Bench for indoor and outdoor use made from 100% recycled plastic, sourced from post-consumer tetrapack packaging.





- Single or double backrest.
- Side armrests.
- Single or double legs.
- Planter.
- · Power adapter.

Metal structure with architectural-quality RAL 7009 epoxy green paint finish, highly resistant to corrosion. Cataphoresis treatment is applied before painting to provide maximum protection for outdoor use.

All materials are 100% recyclable at the end of the item's useful life.

**Maintenance:** Cleaning recommended with a neutral product and damp cloth.





### POLIALUMINIO SPA TECHNICAL SHEET

The polymers used in plastic waste mixtures for manufacturing products are mainly the following:

- HIGH-DENSITY POLYETHYLENE (HDPE) No. 2
- LOW-DENSITY POLYETHYLENE (LDPE) No. 4
- POLYPROPYLENE (PP) No. 5

#### Main characteristics of these polymers


- Recyclable
- Excellent thermal and chemical resistance
- Very good impact resistance
- Flexible
- Density around 0.940-0.970 g/cm³
- Not attacked by acids
- Not attacked by insects and rodents
- Tensile strength N/mm² DIN in ISO 527...28
- Surface hardness N/mm<sup>2</sup> DIN in ISO 2039-1...45
- Thermal conductivity W/m-k DIN 52612...0.38
- Tensile strength N/mm<sup>2</sup> ... 20 30
- Maximum permissible temperature (Celsius) ... 80 100
- Softening temperature (Celsius) 110 140
- Melt flow index 190 degrees C., 2.16 k gf

#### PRECAUTIONS AND WARNINGS

Exposure to high temperatures may cause the product to decompose. During a fire, smoke may contain the original material along with combustion products of varying composition that may be toxic and/or irritating, including carbon monoxide and carbon dioxide (CO2).











































Pol. Ind. Les Guixeres Plàstic, 14 08915 - Badalona T +34 933 950 905



www.unnom.es